



## Operating Instructions Hydrazine Badge (Part Number: 382002)

### Introduction

Hydrazine is a colorless liquid with a penetrating odor resembling that of ammonia. It is extremely destructive to the tissues of the mucous membranes and upper respiratory tract. Symptoms of exposure may include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea and vomiting. OSHA PEL (permissible exposure limit) for hydrazine is 1 ppm (TWA). NIOSH REL (recommended exposure limit) for hydrazine is 0.03 ppm (2 hour ceiling). NIOSH recommends that hydrazine be handled as a potential occupational carcinogen in the workplace.

Hydrazine is used predominantly as a fuel for rocket and jet engines and in the manufacturing of pharmaceuticals. Hydrazine salts are used in refining and as corrosion inhibitors.

### Principle of Operation

The SafeAir hydrazine badge is a monitoring system designed to indicate the presence of hydrazine at concentrations below the permissible exposure limit. The SafeAir hydrazine badge detects the presence of hydrazine by forming a color change in the shape of an exclamation mark inside the triangle. This indication is produced by a color-forming reaction, which occurs when hydrazine reacts with a flat indicator layer.

### Physical Specifications:

Dimensions	74 mm x 41 mm x 1 mm
Weight	1.5 g
Refrigerated shelf life	1 year
Color change	orange to maroon

### Sampling Parameters:

Exposure dose:	
Badge	8 ppb·hr
Badge with color comparator	4.5 – >300 ppb·hr
Minimum detectable limit (8 hours)	1 ppb
Maximum recommended sampling time	2 days
Minimum recommended sampling time	5 minutes
Relative humidity range	23% - 83%
Face velocity range	5 – 168 cm/sec
Temperature range	17°C - 35°C (63°F - 95°F)
Light effect – UV (direct sunlight)	no effect
Light effect – visible	no effect
Color stability	4 weeks
Known Interferences	Monomethyl hydrazine, and aromatic amines

### Operating Instructions

1. Allow the badge to warm to room temperature prior to removing the badge from its protective pouch.
2. For personnel monitoring, attach the badge near the user's breathing zone (i.e. the collar) with the front side exposed to the surrounding atmosphere.
3. For area monitoring, attach the badge to a stand and mount in a centralized area with the front side exposed to the surrounding atmosphere.
4. The exclamation mark appears within the triangle when hydrazine is present. Please note that the exclamation mark will appear underneath the printed exposure dose (sensitivity).
5. To determine the exposure dose, a SafeAir hydrazine color comparator (PN: 383001) is available for use with this badge. To obtain the average concentration, divide the exposure dose (ppb·hr) by the exposure time in hours (hr.).

### **WARRANTY EXCLUSIONS AND LIMITATION OF LIABILITY**

IF THE USER DOES NOT ACCEPT THE FOLLOWING TERMS, THE USER SHOULD NOT USE THE SAFEAIR BADGES AND COLOR COMPARATORS.

Seller warrants that, for the lesser of one (1) year or the shelf-life provided on the Seller's product, its packaging or its literature, its products shall conform to the description of such products as provided on the Seller's product, its packaging or its literature. THIS WARRANTY IS EXCLUSIVE AND SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Seller's warranties made in connection with this sale shall not be effective if Seller has determined, in its sole discretion, that Buyer has misused the products in any manner, has failed to use the products in accordance with safe industry standards and practices, or has failed to use the products in accordance with Seller's written operating instructions, or other instructions furnished by Seller to Buyer.

Seller's sole and exclusive liability and Buyer's exclusive remedy with respect to products to Seller's satisfaction to be defective or nonconforming shall be replacement of such products without charge or refund of the purchase price, in Seller's sole discretion, upon the return of such products in accordance with Seller's instructions. All claims must be brought within one (1) year of shipment, regardless of their nature.

SELLER SHALL NOT IN ANY EVENT BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OF ANY KIND RESULTING FROM ANY USE OR FAILURE OF THE PRODUCTS, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE INCLUDING, WITHOUT LIMITATION, LIABILITY FOR LOSS OF USE, LOSS OF WORK IN PROGRESS, DOWN TIME, LOSS OF REVENUE OR PROFITS, FAILURE TO REALIZE SAVINGS, LOSS OF PRODUCTS OF BUYER OR OTHER USE OF ANY LIABILITY OF BUYER TO A THIRD PARTY ON ACCOUNT OF SUCH LOSS, OR FOR ANY LABOR OR ANY OTHER EXPENSE, DAMAGE OR LOSS OCCASIONED BY SUCH PRODUCT INCLUDING PERSONAL INJURY OR PROPERTY DAMAGE UNLESS SUCH PERSONAL INJURY OR PROPERTY DAMAGE IS CAUSED BY SELLER'S GROSS NEGLIGENCE.

**Warning: Keep out of reach of children. If ingested seeks medical attention immediately.**



www.morphtec.com  
©2017, Morphix Technologies  
All rights reserved  
Publication Number: 01-382002A.9-0921  
US Patent Number: 6,284,198